

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	: Mixture
Product name	: ROSEWOOD CURRANT #EU46272F
UFI	: TP44-34VA-500R-7806
Product code	: EU46272F
Type of product	: Perfumes, fragrances
Product group	: Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category	: Industrial use, Professional use
Industrial/Professional use spec	: Industrial For professional use only
Use of the substance/mixture	: Perfumes, fragrances
Function or use category	: Odour agents

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

FRENCH COLOR & FRAGRANCE International GmbH
Mittlerer Weg 35
DE- 79424 Auggen
Germany
T 49-7631-931-8900
SDS@frenchcolor.com - www.frenchcolor.com

1.4. Emergency telephone number

Emergency number	: 1-800-255-3924; +01-813-248-0585; China:+400-120-0751; Mexico:+01-800-099-0731; Brazil: +0-800-591-6042; India: +000-800-100-4086
------------------	--

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin sensitisation, Category 1	H317
Hazardous to the aquatic environment – Chronic Hazard, Category 2	H411
Full text of H- and EUH-statements: see section 16	


Adverse physicochemical, human health and environmental effects

May cause an allergic skin reaction. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Warning

Contains

: Vertenex; d-Limonene; Triplal (Vertocitral); Pine Needle Oil ; Linalool; Orange oil ; Cedramber; Lavandin abrialis oil; 3-Hepten-2-one, 3,4,5,6,6-pentamethyl-, (Z)-

ROSEWOOD CURRANT #EU46272F

Safety Data Sheet

Hazard statements (CLP)	: H317 - May cause an allergic skin reaction. H411 - Toxic to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P272 - Contaminated work clothing should not be allowed out of the workplace. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P302+P352 - IF ON SKIN: Wash with plenty of water. P321 - Specific treatment (see supplemental first aid instruction on this label).
Extra phrases	: For professional users only.

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Cedarwood oil, Texas	CAS-No.: 68990-83-0 EC-No.: 294-461-7	1.5 – 3	Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Diethyl malonate	CAS-No.: 105-53-3 EC-No.: 203-305-9 REACH-no: 01-2119886972-18	1.1 – 2.2	Eye Irrit. 2, H319
Vertenex	CAS-No.: 32210-23-4 EC-No.: 250-954-9 REACH-no: 01-2119976286-24	1 – 2	Skin Sens. 1B, H317
d-Limonene substance with national workplace exposure limit(s) (DE, ES, FI, SI, NO, CH)	CAS-No.: 5989-27-5 EC-No.: 227-813-5 EC Index-No.: 601-029-00-7;601-096-00-2 REACH-no: 01-2119493353-35	0.7 – 1.3	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1B, H317 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 3, H412
Triplal (Vertocitral)	CAS-No.: 68039-49-6 EC-No.: 268-264-1	0.5 – 0.95375	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 3, H412
Pine Needle Oil	CAS-No.: 8002-09-3 EC-No.: 306-895-7	0.4 – 0.8	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Linalool	CAS-No.: 78-70-6 EC-No.: 201-134-4 EC Index-No.: 603-235-00-2 REACH-no: 01-2119474016-42	0.4 – 0.7	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317

ROSEWOOD CURRANT #EU46272F

Safety Data Sheet

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Sandela	CAS-No.: 66068-84-6 EC-No.: 266-100-3	0.3 – 0.65	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Benzyl benzoate	CAS-No.: 120-51-4 EC-No.: 204-402-9 EC Index-No.: 607-085-00-9 REACH-no: 01-2119976371-33	0.2 – 0.435	Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Orange oil	CAS-No.: 8008-57-9 EC-No.: 232-433-8 REACH-no: 01-2119493353-35	0.2 – 0.3	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Cedramber	CAS-No.: 19870-74-7 EC-No.: 243-384-7	0.2 – 0.3	Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Skin Sens. 1B, H317
Lavandin oil	CAS-No.: 8022-15-9 EC-No.: 617-009-6	0.2 – 0.3	Eye Irrit. 2, H319 Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
Acetyl Diisoamylene	CAS-No.: 81786-73-4 EC-No.: 279-822-9	0.1 – 0.25	Skin Sens. 1B, H317 Aquatic Chronic 2, H411
Citral substance with national workplace exposure limit(s) (BE, ES, IE, PL, PT)	CAS-No.: 5392-40-5 EC-No.: 226-394-6 EC Index-No.: 605-019-00-3 REACH-no: 01-2119462829-23	0 – 0.05	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
.beta.-Pinene substance with national workplace exposure limit(s) (BE, EE, ES, LT, PT, SE, NO)	CAS-No.: 127-91-3 EC-No.: 204-872-5	≤ 0.0225	Flam. Liq. 3, H226
Dipropylene glycol monomethyl ether substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 34590-94-8 EC-No.: 252-104-2	≤ 0.0186	Not classified
.alpha.-Pinene substance with national workplace exposure limit(s) (BE, EE, ES, LT, PT, SE, NO)	CAS-No.: 80-56-8 EC-No.: 201-291-9	≤ 0.0015	Flam. Liq. 3, H226

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Allow the victim to rest.

ROSEWOOD CURRANT #EU46272F

Safety Data Sheet

First-aid measures after skin contact	: If skin irritation occurs: Get medical advice/attention. Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Obtain medical attention if pain, blinking or redness persists. Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Obtain emergency medical attention. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Not expected to present a significant hazard under anticipated conditions of normal use.
Symptoms/effects after skin contact	: May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Sand. Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Toxic fumes may be released.
--	--------------------------------

5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. Evacuate unnecessary personnel. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.
----------------------	--

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	: Collect spillage.
Methods for cleaning up	: Take up liquid spill into absorbent material. Store away from other materials.
Other information	: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

Exposure controls and personal protection. For further information refer to section 13.

ROSEWOOD CURRANT #EU46272F

Safety Data Sheet

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Provide good ventilation in process area to prevent formation of vapour. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Wear personal protective equipment.
Hygiene measures	: Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Keep container closed when not in use. Store in a well-ventilated place. Keep cool.
Incompatible products	: Strong bases. Strong acids.
Incompatible materials	: Sources of ignition. Direct sunlight.
Storage temperature	: 25 °C
Storage area	: Store in a well-ventilated place. Store away from heat.
Special rules on packaging	: Store in a closed container.
Packaging materials	: Do not store in corrodable metal.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

d-Limonene (5989-27-5)	
Finland - Occupational Exposure Limits	
HTP (OEL TWA) [1]	140 mg/m ³
HTP (OEL TWA) [2]	25 ppm
HTP (OEL STEL)	280 mg/m ³
HTP (OEL STEL) [ppm]	50 ppm
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA) [1]	28 mg/m ³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
AGW (OEL TWA) [2]	5 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Chemical category	Skin notation, Skin sensitization
Slovenia - Occupational Exposure Limits	
OEL TWA	28 mg/m ³
OEL TWA [ppm]	5 ppm
OEL STEL	112 mg/m ³
OEL STEL [ppm]	20 ppm
OEL chemical category	Potential for cutaneous absorption
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA) [1]	168 mg/m ³
VLA-ED (OEL TWA) [2]	30 ppm

ROSEWOOD CURRANT #EU46272F

Safety Data Sheet

d-Limonene (5989-27-5)	
OEL chemical category	Sensitizer, skin - potential for cutaneous absorption
Norway - Occupational Exposure Limits	
Greenseverdi (OEL TWA) [1]	140 mg/m ³
Greenseverdi (OEL TWA) [2]	25 ppm
Korttidsverdi (OEL STEL)	175 mg/m ³ (value calculated)
Korttidsverdi (OEL STEL) [ppm]	37.5 ppm (value calculated)
OEL chemical category	Allergenic substance
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA) [1]	40 mg/m ³
MAK (OEL TWA) [2]	7 ppm
KZGW (OEL STEL)	80 mg/m ³
KZGW (OEL STEL) [ppm]	14 ppm
OEL chemical category	Sensitizer
.beta.-Pinene (127-91-3)	
Belgium - Occupational Exposure Limits	
OEL TWA [ppm]	20 ppm
Estonia - Occupational Exposure Limits	
OEL TWA	150 mg/m ³
OEL TWA [ppm]	25 ppm
OEL STEL	300 mg/m ³
OEL STEL [ppm]	50 ppm
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	150 mg/m ³
IPRV (OEL TWA) [ppm]	25 ppm
TPRV (OEL STEL)	300 mg/m ³
TPRV (OEL STEL) [ppm]	50 ppm
Portugal - Occupational Exposure Limits	
OEL TWA [ppm]	20 ppm (Turpentine and selected Monoterpenes)
OEL chemical category	Sensitizer, A4 - Not Classifiable as a Human Carcinogen
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA) [1]	113 mg/m ³
VLA-ED (OEL TWA) [2]	20 ppm
OEL chemical category	Sensitizer
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	150 mg/m ³
NGV (OEL TWA) [ppm]	25 ppm
KTV (OEL STEL)	300 mg/m ³
KTV (OEL STEL) [ppm]	50 ppm
OEL chemical category	Sensitizer

ROSEWOOD CURRANT #EU46272F

Safety Data Sheet

.beta.-Pinene (127-91-3)	
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA) [1]	140 mg/m ³
Grenseverdi (OEL TWA) [2]	25 ppm
Korttidsverdi (OEL STEL)	175 mg/m ³ (value calculated)
Korttidsverdi (OEL STEL) [ppm]	37.5 ppm (value calculated)
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	20 ppm (Turpentine and selected monoterpenes)
ACGIH chemical category	Not Classifiable as a Human Carcinogen, dermal sensitizer
.alpha.-Pinene (80-56-8)	
Belgium - Occupational Exposure Limits	
OEL TWA [ppm]	20 ppm
Estonia - Occupational Exposure Limits	
OEL TWA	150 mg/m ³
OEL TWA [ppm]	25 ppm
OEL STEL	300 mg/m ³
OEL STEL [ppm]	50 ppm
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	150 mg/m ³
IPRV (OEL TWA) [ppm]	25 ppm
TPRV (OEL STEL)	300 mg/m ³
TPRV (OEL STEL) [ppm]	50 ppm
Portugal - Occupational Exposure Limits	
OEL TWA [ppm]	20 ppm (Turpentine and selected Monoterpenes)
OEL chemical category	Sensitizer, A4 - Not Classifiable as a Human Carcinogen
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA) [1]	113 mg/m ³
VLA-ED (OEL TWA) [2]	20 ppm
OEL chemical category	Sensitizer
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	150 mg/m ³
NGV (OEL TWA) [ppm]	25 ppm
KTV (OEL STEL)	300 mg/m ³
KTV (OEL STEL) [ppm]	50 ppm
OEL chemical category	Sensitizer
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA) [1]	140 mg/m ³
Grenseverdi (OEL TWA) [2]	25 ppm
Korttidsverdi (OEL STEL)	175 mg/m ³ (value calculated)
Korttidsverdi (OEL STEL) [ppm]	37.5 ppm (value calculated)

ROSEWOOD CURRANT #EU46272F

Safety Data Sheet

.alpha.-Pinene (80-56-8)	
OEL chemical category	Skin notation
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	20 ppm (Turpentine and selected monoterpenes)
ACGIH chemical category	Not Classifiable as a Human Carcinogen, dermal sensitizer
Dipropylene glycol monomethyl ether (34590-94-8)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	308 mg/m ³
IOEL TWA [ppm]	50 ppm
Remark	Possibility of significant uptake through the skin
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	307 mg/m ³ (mixed isomers)
MAK (OEL TWA) [ppm]	50 ppm (mixed isomers)
MAK (OEL STEL)	614 mg/m ³ (isomers mixtures)
MAK (OEL STEL) [ppm]	100 ppm (isomers mixtures)
OEL chemical category	Skin notation
Belgium - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
OEL TWA [ppm]	50 ppm
OEL chemical category	Skin, Skin notation
Bulgaria - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
OEL TWA [ppm]	50 ppm
Croatia - Occupational Exposure Limits	
GVI (OEL TWA) [1]	308 mg/m ³
GVI (OEL TWA) [2]	50 ppm
OEL chemical category	Skin notation
Cyprus - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
OEL TWA [ppm]	50 ppm
OEL chemical category	Skin-potential for cutaneous absorption
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	270 mg/m ³
OEL chemical category	Potential for cutaneous absorption
Denmark - Occupational Exposure Limits	
OEL TWA [1]	309 mg/m ³
OEL TWA [2]	50 ppm
OEL chemical category	Potential for cutaneous absorption
Estonia - Occupational Exposure Limits	
OEL TWA	308 mg/m ³

ROSEWOOD CURRANT #EU46272F

Safety Data Sheet

Dipropylene glycol monomethyl ether (34590-94-8)	
OEL TWA [ppm]	50 ppm
OEL chemical category	Skin notation
Finland - Occupational Exposure Limits	
HTP (OEL TWA) [1]	310 mg/m ³
HTP (OEL TWA) [2]	50 ppm
OEL chemical category	Potential for cutaneous absorption
France - Occupational Exposure Limits	
VME (OEL TWA)	308 mg/m ³ (restrictive limit)
VME (OEL TWA) [ppm]	50 ppm (restrictive limit)
OEL chemical category	Risk of cutaneous absorption
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA) [1]	310 mg/m ³ (isomer mixture)
AGW (OEL TWA) [2]	50 ppm (isomer mixture)
Gibraltar - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
OEL TWA [ppm]	50 ppm
OEL chemical category	Skin notation
Greece - Occupational Exposure Limits	
OEL TWA	600 mg/m ³
OEL TWA [ppm]	100 ppm
OEL STEL	900 mg/m ³
OEL STEL [ppm]	150 ppm
OEL chemical category	skin - potential for cutaneous absorption
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	308 mg/m ³
Ireland - Occupational Exposure Limits	
OEL TWA [1]	308 mg/m ³ ((2-Methoxymethylethoxy)propanol)
OEL TWA [2]	50 ppm ((2-Methoxymethylethoxy)propanol)
OEL STEL	924 mg/m ³ (calculated (2-(2-Methoxypropoxy)-1-propanol)
OEL STEL [ppm]	150 ppm (calculated (2-(2-Methoxypropoxy)-1-propanol)
OEL chemical category	Potential for cutaneous absorption
Italy - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
OEL TWA [ppm]	50 ppm
OEL chemical category	skin - potential for cutaneous absorption
Latvia - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
OEL TWA [ppm]	50 ppm
OEL chemical category	skin - potential for cutaneous exposure

ROSEWOOD CURRANT #EU46272F

Safety Data Sheet

Dipropylene glycol monomethyl ether (34590-94-8)	
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	300 mg/m ³ (2-(2-Methoxypropoxy)-propanol)
IPRV (OEL TWA) [ppm]	50 ppm (2-(2-Methoxypropoxy)-propanol)
TPRV (OEL STEL)	450 mg/m ³ (2-(2-Methoxypropoxy)-propanol)
TPRV (OEL STEL) [ppm]	75 ppm (2-(2-Methoxypropoxy)-propanol)
OEL chemical category	Skin notation
Luxembourg - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
OEL TWA [ppm]	50 ppm
OEL chemical category	Possibility of significant uptake through the skin
Malta - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
OEL TWA [ppm]	50 ppm
OEL chemical category	Possibility of significant uptake through the skin
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	300 mg/m ³
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	240 mg/m ³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol and 2-(2-Methoxy-1-methylethoxy)propan-1-ol)
NDSch (OEL STEL)	480 mg/m ³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol)
Portugal - Occupational Exposure Limits	
OEL TWA	308 mg/m ³ (indicative limit value)
OEL TWA [ppm]	50 ppm (indicative limit value)
OEL STEL [ppm]	150 ppm
OEL chemical category	skin - potential for cutaneous exposure indicative limit value
Romania - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
OEL TWA [ppm]	50 ppm
OEL chemical category	Skin notation
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA) [1]	308 mg/m ³
NPHV (OEL TWA) [2]	50 ppm
OEL chemical category	Potential for cutaneous absorption
Slovenia - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
OEL TWA [ppm]	50 ppm
OEL STEL	308 mg/m ³
OEL STEL [ppm]	50 ppm
OEL chemical category	Potential for cutaneous absorption

ROSEWOOD CURRANT #EU46272F

Safety Data Sheet

Dipropylene glycol monomethyl ether (34590-94-8)	
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA) [1]	308 mg/m ³ (indicative limit value)
VLA-ED (OEL TWA) [2]	50 ppm (indicative limit value)
OEL chemical category	skin - potential for cutaneous absorption
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	300 mg/m ³
NGV (OEL TWA) [ppm]	50 ppm
KTV (OEL STEL)	450 mg/m ³
KTV (OEL STEL) [ppm]	75 ppm
OEL chemical category	Skin notation
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	308 mg/m ³
WEL TWA (OEL TWA) [2]	50 ppm
WEL STEL (OEL STEL)	924 mg/m ³ (calculated)
WEL STEL (OEL STEL) [ppm]	150 ppm (calculated)
WEL chemical category	Potential for cutaneous absorption
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA) [1]	300 mg/m ³
Grenseverdi (OEL TWA) [2]	50 ppm
Korttidsverdi (OEL STEL)	375 mg/m ³ (value calculated)
Korttidsverdi (OEL STEL) [ppm]	75 ppm (value calculated)
OEL chemical category	Skin notation
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA) [1]	300 mg/m ³ (aerosol, vapour)
MAK (OEL TWA) [2]	50 ppm (aerosol, vapour)
KZGW (OEL STEL)	300 mg/m ³ (aerosol, vapour)
KZGW (OEL STEL) [ppm]	50 ppm (aerosol, vapour)
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	100 ppm
ACGIH OEL STEL [ppm]	150 ppm
ACGIH chemical category	Skin - potential significant contribution to overall exposure by the cutaneous route
Citral (5392-40-5)	
Belgium - Occupational Exposure Limits	
OEL TWA	32 mg/m ³ (vapor and aerosol)
OEL TWA [ppm]	5 ppm (vapor and aerosol)
OEL chemical category	Skin
Ireland - Occupational Exposure Limits	
OEL TWA [2]	5 ppm
OEL STEL [ppm]	15 ppm (calculated)

ROSEWOOD CURRANT #EU46272F

Safety Data Sheet

Citral (5392-40-5)	
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	27 mg/m ³
NDSch (OEL STEL)	54 mg/m ³
Portugal - Occupational Exposure Limits	
OEL TWA [ppm]	5 ppm
OEL chemical category	Sensitizer, A4 - Not Classifiable as a Human Carcinogen, skin - potential for cutaneous exposure
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA) [2]	5 ppm (inhalable fraction and vapor)
OEL chemical category	Sensitizer, skin - potential for cutaneous absorption
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	5 ppm (inhalable fraction and vapor)
ACGIH chemical category	Not Classifiable as a Human Carcinogen, Skin - potential significant contribution to overall exposure by the cutaneous route, dermal sensitizer

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Chemical goggles or safety glasses. Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Wear protective gloves.

ROSEWOOD CURRANT #EU46272F

Safety Data Sheet

8.2.2.3. Respiratory protection

Respiratory protection:

Wear appropriate mask

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: light yellow. amber. Conforms to standard.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 91 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: 0.949
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Extremely high or low temperatures.

ROSEWOOD CURRANT #EU46272F

Safety Data Sheet

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Carbon dioxide.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Diethyl malonate (105-53-3)

LD50 oral rat	14900 µl/kg
LD50 dermal rabbit	> 16960 mg/kg

Vertenex (32210-23-4)

LD50 oral rat	5 g/kg
LD50 oral	3370 mg/kg bodyweight
LD50 dermal rabbit	> 5000 mg/kg

d-Limonene (5989-27-5)

LD50 oral rat	4400 mg/kg
LD50 dermal rabbit	> 5 g/kg

Triplal (Vertocitral) (68039-49-6)

LD50 oral	3900 mg/kg bodyweight
-----------	-----------------------

Pine Needle Oil (8002-09-3)

LD50 oral rat	3200 mg/kg
LD50 oral	3200 mg/kg bodyweight
LD50 dermal rabbit	400 mg/kg
LC50 Inhalation - Rat	> 3.79 mg/l/4h

Linalool (78-70-6)

LD50 oral	2790 mg/kg bodyweight
-----------	-----------------------

Sandela (66068-84-6)

LD50 dermal rat	> 2000 mg/kg
LC50 Inhalation - Rat	> 5.27 mg/l/4h

Benzyl benzoate (120-51-4)

LD50 oral rat	500 mg/kg
LD50 oral	1160 mg/kg bodyweight
LD50 dermal rabbit	4000 mg/kg

Orange oil (8008-57-9)

LD50 oral rat	4400 mg/kg
LD50 dermal rabbit	> 5000 mg/kg

ROSEWOOD CURRANT #EU46272F

Safety Data Sheet

Lavandin oil (8022-15-9)	
LD50 oral rat	> 5 g/kg
.beta.-Pinene (127-91-3)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
.alpha.-Pinene (80-56-8)	
LD50 oral rat	3700 mg/kg
LD50 oral	500 mg/kg bodyweight
LD50 dermal rat	> 5000 mg/kg
Dipropylene glycol monomethyl ether (34590-94-8)	
LD50 oral rat	5.35 g/kg
LD50 dermal rabbit	9500 mg/kg
Citral (5392-40-5)	
LD50 oral rat	4960 mg/kg
LD50 dermal rabbit	2250 mg/kg
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
d-Limonene (5989-27-5)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Benzyl benzoate (120-51-4)	
Viscosity, kinematic	7.456 mm ² /s
Orange oil (8008-57-9)	
Hydrocarbon	Yes
Potential adverse human health effects and symptoms	: Based on available data, the classification criteria are not met

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects.

Diethyl malonate (105-53-3)	
LC50 - Fish [1]	10.3 – 13.4 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 - Crustacea [1]	202.3 mg/l (Exposure time: 48 h - Species: Daphnia magna)

ROSEWOOD CURRANT #EU46272F

Safety Data Sheet

Diethyl malonate (105-53-3)	
EC50 72h - Algae [1]	508.2 mg/l (Species: Desmodesmus subspicatus)
Vertenex (32210-23-4)	
LC50 - Fish [1]	8.6 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [semi-static])
d-Limonene (5989-27-5)	
LC50 - Fish [1]	0.619 – 0.796 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 - Fish [2]	35 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
Pine Needle Oil (8002-09-3)	
EC50 - Crustacea [1]	17 – 28 mg/l (Exposure time: 48 h - Species: Daphnia magna [Flow through])
Linalool (78-70-6)	
EC50 96h - Algae [1]	88.3 mg/l (Species: Desmodesmus subspicatus)
Benzyl benzoate (120-51-4)	
LC50 - Fish [1]	2.32 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static])
NOEC (chronic)	0.168 mg/l
.alpha.-Pinene (80-56-8)	
LC50 - Fish [1]	0.28 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 - Crustacea [1]	41 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Dipropylene glycol monomethyl ether (34590-94-8)	
LC50 - Fish [1]	> 10000 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 - Crustacea [1]	1919 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Citral (5392-40-5)	
EC50 - Crustacea [1]	7 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h - Algae [1]	16 mg/l (Species: Desmodesmus subspicatus)
EC50 96h - Algae [1]	19 mg/l (Species: Desmodesmus subspicatus)

12.2. Persistence and degradability

ROSEWOOD CURRANT #EU46272F	
Persistence and degradability	Not established.
Cedarwood oil, Texas (68990-83-0)	
Persistence and degradability	Not established.
Benzyl benzoate (120-51-4)	
Persistence and degradability	May cause long-term adverse effects in the environment.

12.3. Bioaccumulative potential

ROSEWOOD CURRANT #EU46272F	
Bioaccumulative potential	Not established.
Cedarwood oil, Texas (68990-83-0)	
Bioaccumulative potential	Not established.

ROSEWOOD CURRANT #EU46272F

Safety Data Sheet

Diethyl malonate (105-53-3)	
Partition coefficient n-octanol/water (Log Pow)	0.96
Vertenex (32210-23-4)	
Partition coefficient n-octanol/water (Log Pow)	4.8 (at 25 °C)
d-Limonene (5989-27-5)	
Partition coefficient n-octanol/water (Log Pow)	4.38 (at 37 °C (at pH 7.2))
Benzyl benzoate (120-51-4)	
Partition coefficient n-octanol/water (Log Pow)	3.97 (at 25 °C)
Bioaccumulative potential	Not established.
.alpha.-Pinene (80-56-8)	
Partition coefficient n-octanol/water (Log Pow)	4.1
Dipropylene glycol monomethyl ether (34590-94-8)	
Partition coefficient n-octanol/water (Log Pow)	0.35 (at 25 °C (at pH 7))
Citral (5392-40-5)	
Partition coefficient n-octanol/water (Log Pow)	2.76 (at 25 °C)

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Additional information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods






Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	: Avoid release to the environment.
HP Code	: HP3 - "Flammable:" <ul style="list-style-type: none">- flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;- flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;- flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;- flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa;- water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;- other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.
	HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

ROSEWOOD CURRANT #EU46272F

Safety Data Sheet

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
UN 3082	UN 3082	UN 3082	UN 3082	UN 3082
14.2. UN proper shipping name				
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Cedarwood oil, Texas)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Cedarwood oil, Texas)	Environmentally hazardous substance, liquid, n.o.s. (Cedarwood oil, Texas)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Cedarwood oil, Texas)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Cedarwood oil, Texas)
Transport document description				
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Cedarwood oil, Texas), 9, III, (-)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Cedarwood oil, Texas), 9, III, MARINE POLLUTANT	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (Cedarwood oil, Texas), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Cedarwood oil, Texas), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Cedarwood oil, Texas), 9, III
14.3. Transport hazard class(es)				
9	9	9	9	9
				
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available				

14.6. Special precautions for user


Overland transport

Classification code (ADR)	: M6
Special provisions (ADR)	: 274, 335, 375, 601
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBV
Vehicle for tank carriage	: AT
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV13

ROSEWOOD CURRANT #EU46272F

Safety Data Sheet

Hazard identification number (Kemler No.) : 90
Orange plates :



Tunnel restriction code (ADR) : -
EAC code : •3Z

Transport by sea

Special provisions (IMDG) : 274, 335, 969
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E1
Packing instructions (IMDG) : LP01, P001
Special packing provisions (IMDG) : PP1
IBC packing instructions (IMDG) : IBC03
Tank instructions (IMDG) : T4
Tank special provisions (IMDG) : TP1, TP29
EmS-No. (Fire) : F-A
EmS-No. (Spillage) : S-F
Stowage category (IMDG) : A

Air transport

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y964
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 964
PCA max net quantity (IATA) : 450L
CAO packing instructions (IATA) : 964
CAO max net quantity (IATA) : 450L
Special provisions (IATA) : A97, A158, A197, A215
ERG code (IATA) : 9L

Inland waterway transport

Classification code (ADN) : M6
Special provisions (ADN) : 274, 335, 375, 601
Limited quantities (ADN) : 5 L
Excepted quantities (ADN) : E1
Equipment required (ADN) : PP
Number of blue cones/lights (ADN) : 0

Rail transport

Classification code (RID) : M6
Special provisions (RID) : 274, 335, 375, 601
Limited quantities (RID) : 5L
Excepted quantities (RID) : E1
Packing instructions (RID) : P001, IBC03, LP01, R001
Special packing provisions (RID) : PP1
Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions (RID) : T4
Portable tank and bulk container special provisions (RID) : TP1, TP29
Tank codes for RID tanks (RID) : LGBV
Transport category (RID) : 3
Special provisions for carriage – Packages (RID) : W12
Special provisions for carriage - Loading, unloading and handling (RID) : CW13, CW31
Colis express (express parcels) (RID) : CE8
Hazard identification number (RID) : 90

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

ROSEWOOD CURRANT #EU46272F

Safety Data Sheet

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(a)	d-Limonene ; Orange oil ; .beta.-Pinene ; .alpha.- Pinene	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	ROSEWOOD CURRANT #EU46272F ; Cedarwood oil, Texas ; Diethyl malonate ; Vertenex ; d- Limonene ; Triplal (Vertocitral) ; Pine Needle Oil ; Linalool ; Sandela ; Benzyl benzoate ; Orange oil ; Cedramber ; Lavandin oil ; Acetyl Diisoamylene ; Citral	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	ROSEWOOD CURRANT #EU46272F ; Cedarwood oil, Texas ; d-Limonene ; Triplal (Vertocitral) ; Pine Needle Oil ; Sandela ; Benzyl benzoate ; Orange oil ; Cedramber ; Lavandin oil ; Acetyl Diisoamylene	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
40.	d-Limonene ; Orange oil ; .beta.-Pinene ; .alpha.- Pinene	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

ROSEWOOD CURRANT #EU46272F

Safety Data Sheet

15.1.2. National regulations

Germany

- Employment restrictions : Observe restrictions according Act on the Protection of Working Mothers (MuSchG).
Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG).
- Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).
- Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

- ABM category : A(2) - toxic for aquatic organisms, may have longterm hazardous effects in aquatic environment
- SZW-lijst van kankerverwekkende stoffen : Cedarwood oil, Texas, Triplal (Vertocitral), Pine Needle Oil, Sandela, Orange oil are listed
- SZW-lijst van mutagene stoffen : Triplal (Vertocitral), Pine Needle Oil, Sandela, Orange oil are listed
- SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed
- SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed
- SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

Denmark

- Class for fire hazard : Class III-1
- Store unit : 50 liter
- Classification remarks : Flammable according to the Danish Ministry of Justice; Emergency management guidelines for the storage of flammable liquids must be followed
- Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

Switzerland

- Storage class (LK) : LK 10/12 - Liquids

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods

ROSEWOOD CURRANT #EU46272F

Safety Data Sheet

Abbreviations and acronyms:	
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Other information : None.

Full text of H- and EUH-statements:	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

ROSEWOOD CURRANT #EU46272F

Safety Data Sheet

Full text of H- and EUH-statements:

H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.